

NANO EXPRESS

Open Access

Self-ordered TiO₂ quantum dot array prepared via anodic oxidation

Jana Drbohlavova^{1,4*}, Marina Vorozhtsova¹, Radim Hrdy^{1,4}, Rene Kizek^{2,4}, Ota Salyk³ and Jaromir Hubalek^{1,4*}

Abstract

The template-based methods belong to low-cost and rapid preparation techniques for various nanostructures like nanowires, nanotubes, and nanodots or even quantum dots [QDs]. The nanostructured surfaces with QDs are very promising in the application as a sensor array, also called 'fluorescence array detector.' In particular, this new sensing approach is suitable for the detection of various biomolecules (DNA, proteins) *in vitro* (in clinical diagnostics) as well as for *in vivo* imaging.

The paper deals with the fabrication of TiO₂ planar nanostructures (QDs) by the process of titanium anodic oxidation through an alumina nanoporous template on a silicon substrate. Scanning electron microscopy observation showed that the average diameter of TiO₂ QDs is less than 10 nm. Raman spectroscopic characterization of self-organized titania QDs confirmed the presence of an anatase phase after annealing at 400°C in vacuum. Such heat-treated TiO₂ QDs revealed a broad emission peak in the visible range (characterized by fluorescence spectroscopy).

Keywords: quantum dots, biosensing, TiO₂, template methods, nanoporous mask

Background

Semiconductor quantum dots [QDs] with exceptional physical and optical properties are favorable fluorescent markers in medicine, where they can serve as biosensors and labels in biological imaging [1-3]. Commonly, QDs are used in colloidal form (in aqueous solution) [4,5]. Nowadays, there is a demand for QDs deposited on various solid supports. Nevertheless, directly grown QDs in planar form (so-called lab-on-chip) for *in situ* biosensing purposes are studied very rarely [6]. Occasionally, the scientists try to encapsulate the colloidal QDs in some matrix, e.g., from polymeric compounds [7].

The deposited nanostructures are mostly fabricated through traditional top-down patterning methods like epitaxy or lithographic techniques (mainly photolithography and e-beam lithography), which are expensive and time-consuming. Contrary to these methods, the template-based technique seems to be more convenient for nanostructured material synthesis since it is affordable and provides reproducible results. Concerning the

template, nanoporous alumina belongs to the most extensively studied materials [8].

The biocompatibility of QDs used for medicinal purposes is usually a problematic issue because most of them are toxic (due to the cadmium ion content), which poses a potential danger especially for future medical applications. Using QDs prepared from titanium dioxide prevents this difficulty because TiO₂ is a non-toxic material. Nevertheless, there are no scientific papers about the preparation and application of deposited TiO₂ QDs (only nanodots without the quantum confinement effect). Final quantum confinement of TiO₂ QDs strongly depends on the anatase/rutile phase composition [9,10]. The phase development of TiO₂ nanodots is much different from that of TiO₂ thin films and powders. Generally, the nanodots are polycrystalline and consist of a mixed phase of anatase and rutile after high temperature annealing. However, Chen et al. revealed that TiO₂ nanodots with a single anatase phase can be prepared from an epitaxial Al/TiN bilayered film on a sapphire substrate by electrochemical anodization of the TiN layer using a nanoporous anodic alumina film as the template [11].

* Correspondence: drbohla@feec.vutbr.cz; hubalek@feec.vutbr.cz

¹Department of Microelectronics, Faculty of Electrical Engineering and Communication, Brno University of Technology, Technická 10, Brno 61600, Czech Republic

Full list of author information is available at the end of the article

In this work, we modified the experimental method of Chen et al. for the fabrication of TiO₂ nanodots to prepare a TiO₂ QD array on silicon substrate with dimensions required to reach the quantum size effect. The key point in our preparation process was to determine the appropriate anodizing potential and deposition time to ensure the optimal nanostructure dimensions, which is necessary from the quantum confinement point of view, as mentioned above. The choice of optimal electrolyte is also significant in order to avoid the possible contamination of the product. The physical, chemical, and luminescence properties of TiO₂ QDs are discussed as well.

Methods

Chemicals

All chemicals such as sulfuric acid (97%, pro analysi [p.a.]), phosphoric acid (84%, p.a.), isopropanol (99.8%, p.a.), and chromium trioxide (99%, p.a.) were purchased from Penta (Prague, Czech Republic). Deionized water underwent demineralization by reverse osmosis using the instrument Aqua Osmotic 02 (Aqua Osmotic, Tisnov, Czech Republic) and subsequent purification using the Millipore RG system and Milli Q water (18.2 MΩ; Millipore Corp., Billerica, MA, USA).

Titanium and aluminum layer preparation

Prior to titanium deposition, the wafers were degreased and cleaned in isopropanol, rinsed out with deionized water, and finally treated with plasma. A high-purity titanium layer (99.995%, Safina, Jesenice, Czech Republic) with a thickness of 100 nm was prepared by tetrode sputtering on a 4-inch silicon wafer previously coated with a SiO₂ layer (prepared by thermal CVD). Subsequently, a high-purity aluminum layer (99.99+%) with a thickness of 1 μm was deposited by thermal evaporation (PVD).

Anodization process

Ordered arrays of titania QDs were achieved by successive anodization of aluminum and titanium layers using the utility model equipment for electrochemical post-processing deposition fabricated in our laboratory (a detailed description of the tool is reported by Hubalek et al. [12]). Thanks to the different anodizing behavior of these layers, the same electrolyte can be applied during the whole process. A concentration of 3 M sulfuric acid was chosen as electrolyte in a constant potential mode (4 V) at 11°C. This acid provides a smaller pore diameter in the alumina template compared to other commonly used electrolytes (oxalic or phosphoric acids). An aqueous solution of H₃PO₄ (50 ml L⁻¹) and CrO₃ (30 g L⁻¹) was used for chemical etching of the alumina template (5 min at 60°C).

Characterization of physical and chemical properties

The size of the QDs was estimated using scanning electron microscopy Mira II MLU (Tescan Mira, Brno, Czech Republic). The topography of the pure Ti layer was analyzed by atomic force microscopy [AFM] (Agilent 5500, Agilent Technologies, Santa Clara, CA, USA) with a 10-nm SiC tip. The phase composition of TiO₂ QDs was characterized by Raman spectroscopy (Renishaw, Wotton-under-Edge, UK) with a NIR laser operating at 745 nm.

Results and discussion

The array of TiO₂ QDs for biosensing application was prepared through a one-step anodization technique using a nanoporous alumina template. The choice of optimal anodization conditions (4 V, 11°C, and 3 M sulfuric acid as electrolyte) resulted in a template pore size in the range of 5 to 8 nm, which enabled the formation of TiO₂ QDs with dimensions of about 8 to 10 nm (confirmed by SEM). According to Monticone et al., this dimension of TiO₂ QDs seems to be appropriate to reach the quantum size effect because they observed almost no variation of the band gap energy with the particle size 2R down to 15 nm [13]. The SEM characterization of the alumina template and TiO₂ QDs provided important information about QD ordering and homogeneity (see Figure 1a, b, respectively). The pores as well as the QDs were hexagonally arranged as we expected. The interpore spacing in the template was estimated at approximately 15 nm. Figure 1c clearly shows Ti grains in the sputtered titanium layer with a thickness of 100 nm before aluminum layer deposition. These titanium grains are also visible under TiO₂ QDs as can be seen on Figure 1b. The titanium surface was also analyzed by AFM with a 10-nm tip (see Figure 1d), but this method was not as accurate as the SEM characterization in our case. Particularly, AFM shows the titanium grains as having overlapped and merged structures. From this reason, AFM with a 10-nm tip is not appropriate for the characterization of our sample with TiO₂ QDs.

Annealing of QDs at 400°C after alumina template dissolution in the mixture of CrO₃ and H₃PO₄ resulted in the transformation of amorphous titanium dioxide into a crystallographic form. The crystallographic phase composition was characterized by Raman spectroscopy (see Figure 2). The Raman spectrum shows two characteristic anatase peaks: the one at 537 cm⁻¹, which is typically presented at 520 cm⁻¹ (corresponding to the A_{1g} and B_{1g} vibrational mode) and the other at 640 cm⁻¹ (corresponding to the E_g vibrational mode). Generally, Raman spectra can be affected by the chemical and structural inhomogeneities, which cause the shifts in the corresponding position of Raman bands [14]. Some modifications in band




Figure 1 SEM and AFM images. SEM characterization of the (a) alumina template, (b) TiO_2 QDs on Ti grains, and (c) Ti layer. (d) AFM image of the Ti layer.

position can be also attributed to the reduction in TiO_2 particle size, phonon confinement, and oxygen deficiency. From the chemical purity point of view, the sample with TiO_2 QDs was characterized by EDX, which confirmed the presence of the Ti, Si, and O elements corresponding to TiO_2 QDs, Ti and SiO_2 layers, and Si wafer.

The photoluminescence properties of the prepared TiO_2 QDs array were characterized by fluorescence spectroscopy. Figure 3 representing the fluorescent spectrum

of annealed the TiO_2 QDs shows a broad emission peak in the range of 440 nm up to 580 nm, while the spectrum of the as-prepared TiO_2 QDs without annealing shows no peaks, which means that this sample is composed predominantly from amorphous TiO_2 .

Conclusion

The cheap, rapid, and easy reproducible template-based method was used successfully for the synthesis of titania




Figure 2 Raman spectra of annealed and non-annealed TiO_2 QDs.

Republic.³ Institute of Physical and Applied Chemistry, Faculty of Chemistry, Brno University of Technology, Brno 61200, Czech Republic⁴ Central European Institute of Technology, Brno University of Technology, Technická 10, 61600 Brno, Czech Republic

Authors' contributions

JD carried out the fabrication of titania QDs and their characterization using Raman and fluorescence spectroscopies. MV participated in the fabrication of QDs array. RH carried out the SEM characterization. RK drafted the manuscript. OS carried out the deposition of metallic layers. JH participated in the design of the fluorescence array detector. All authors read and approved the final manuscript.

Competing interests

The authors declare that they have no competing interests.

Received: 5 November 2010 Accepted: 14 February 2012

Published: 14 February 2012

References

1. Drummen GPC: Quantum Dots - From Synthesis to Applications in Biomedicine and Life Sciences. *Int J Mol Sci* 2010, **11**:154-163.
2. Chen C, Peng J, Xia HS, Wu QS, Zeng LB: Quantum-dot-based immunofluorescent imaging of HER2 and ER provides new insights into breast cancer heterogeneity. *Nanotechnology* 2010, **21**:6.
3. Chomoucka J, Drbohlavova J, Adam V, Kizek R, Hubalek J: Synthesis of Glutathione-coated Quantum Dots. In *2009 32nd International Spring Seminar on Electronics Technology; 2009, Brno*. Edited by: Prášek J, Adámek M, Szeniduch I: leee; 2009:653-657.
4. Oh JK: Surface modification of colloidal CdX-based quantum dots for biomedical applications. *J Mater Chem* 2010, **20**:8433-8445.
5. Veilleux V, Lachance-Quirion D, Dore K, Landry DB, Charette PG: Strain-induced effects in colloidal quantum dots: lifetime measurements and blinking statistics. *Nanotechnology* 2010, **21**:6.
6. Drbohlavova J, Adam V, Kizek R, Hubalek J: Quantum Dots - Characterization, Preparation and Usage in Biological Systems. *Int J Mol Sci* 2009, **10**:656-673.
7. Bodas D, Khan-Malek C: Direct patterning of quantum dots on structured PDMS surface. *Sens Actuator B-Chem* 2007, **128**:168-172.
8. Bao SJ, Li CM, Zang JF, Cui XQ, Qiao Y: New nanostructured TiO_2 for direct electrochemistry and glucose sensor applications. *Adv Func Mater* 2008, **18**:591-599.
9. Naicker PK, Cummings PT, Zhang HZ, Banfield JF: Characterization of titanium dioxide nanoparticles using molecular dynamics simulations. *J Phys Chem B* 2005, **109**:15243-15249.
10. Peng HW, Li JB, Li SS, Xia JB: First-principles study on rutile TiO_2 quantum dots. *J Phys Chem C* 2008, **112**:13964-13969.
11. Chen PL, Kuo CT, Pan FM, Tsai TG: Preparation and phase transformation of highly ordered TiO_2 nanodot arrays on sapphire substrates. *Appl Phys Lett* 2004, **84**:3888-3890.
12. Hubalek J, Hrdy R, Vorozhtsova M: A new tool for the post-process modification of chips by nanostructures for chemical sensing. In *Proceedings of the Eurosensors XXXIII Conference 06-09 September, 2009; Lausanne, Switzerland*. Edited by: Brugger J, Briand D. Elsevier Science Bv; 2009:36-39.
13. Monticone S, Tufeu R, Kanaev AV, Scolan E, Sanchez C: Quantum size effect in TiO_2 nanoparticles: does it exist? *Appl Surf Sci* 2000, **162**-163:565-570.
14. Mazza T, Barborini E, Piseri P, Milani P, Cattaneo D: Raman spectroscopy characterization of TiO_2 rutile nanocrystals. *Phys Rev B* 2007, **75**:045416.

doi:10.1186/1556-276X-7-123

Cite this article as: Drbohlavova et al.: Self-ordered TiO_2 quantum dot array prepared via anodic oxidation. *Nanoscale Research Letters* 2012 **7**:123.




Figure 3 Fluorescence spectra of annealed and non-annealed TiO_2 QDs.

QD sensor array suitable for various biomolecule (DNA, proteins) sensing *in vitro*. The anodization process through the highly ordered alumina nanoporous template provided less than 10-nm-sized TiO_2 QDs densely covering the titanium surface and showing the strong photoluminescence peak in the visible range. The usage of this fluorescence array detector may be of great importance for clinical diagnostics and *in vivo* imaging.

Acknowledgements

The financial support from the grants GACR P102/10/P618, KAN 208130801 and CEITEC CZ.1.05/1.1.00/02.0068 is highly acknowledged.

Author details

¹Department of Microelectronics, Faculty of Electrical Engineering and Communication, Brno University of Technology, Technická 10, Brno 61600, Czech Republic ²Department of Chemistry and Biochemistry, Faculty of Agronomy, Mendel University in Brno, Zemědělská 1, Brno 61300, Czech